



CODE DESCRIPTION STRUCTURE

QC			G1/2	M/F	DN12,5	1	B
Type of coupling							
ISO 7241/A							
Ends							
ISO 1179-1	ASME B1.20.1	ISO 11926-1					
BSPP	NPT	(SAE J1926-1)					
		ORB					
G 1/4	N 1/4	SAE4					
G 3/8	N 3/8	SAE6					
G 1/2	N 1/2	SAE8					
G 3/4	N 3/4	SAE12					
G 1	N 1	SAE16					
G 1 1/4	N 1 1/4	SAE20					
G 1 1/2	N 1 1/2	SAE24					
G 2	N 2	SAE32					
MALE							
FEMALE							
DN/ISO							
6,3							
10							
12,5							
20							
25							
31,5							
40							
50							
Body Material							
● 1 = 1,0737							
● 4 = 1,4404							
Seal material							
● B = NBR E = FKM*							
● E = FKM							


*On request

- Plugs
- Caps



Available colours:

- Blue
- Yellow
- Red
- Green



QUICK COUPLINGS ISO 7241/A (male / female) FEMALE THREAD ISO 1179-1 BSPP WITH POPPET

									CS Carbon Steel										SS Stainless Steel
TYPE	DN	PN	ØA	C	Ød	ch	ØM	WEIGHT	ITEM CODE	TYPE	DN	PN	ØA	C	Ød	ch	ØM	WEIGHT	ITEM CODE
QC ISO A G 1/4 MALE	6.3	MPa 42	mm - 35,5 11,86 19					kg 0,037	NC01G010000	QC ISO A G 1/4 MALE	6.3	MPa 30	mm - 34 11,8 19					kg 0,037	NC01G010001
		Psi 6090	inch - 1,40 0,47 0,75				G1/4	lb 0,08				Psi 4350	inch - 1,34 0,46 0,75				G1/4	lb 0,08	
QC ISO A G 1/4 FEMALE	6.3	MPa 42	mm 25 49,6 - 19					kg 0,11	NC02G010000	QC ISO A G 1/4 FEMALE	6.3	MPa 30	mm 26 58,5 - 19					kg 0,11	NC02G010001
		Psi 6090	inch 0,98 1,95 - 0,75				G1/4	lb 0,24				Psi 4350	inch 1,02 2,30 - 0,75				G1/4	lb 0,24	
QC ISO A G 3/8 MALE	10	MPa 42	mm - 39,5 17,3 22					kg 0,05	NC01G020000	QC ISO A G 3/8 MALE	10	MPa 25	mm - 40 17,3 22					kg 0,05	NC01G02S000
		Psi 6090	inch - 1,56 0,68 0,87				G3/8	lb 0,11				Psi 3625	inch - 1,57 0,68 0,87				G3/8	lb 0,11	
QC ISO A G 3/8 FEMALE	10	MPa 42	mm 32 57 - 22					kg 0,15	NC02G020000	QC ISO A G 3/8 FEMALE	10	MPa 25	mm 30 64 - 22					kg 0,15	NC02G02S000
		Psi 6090	inch 1,26 2,24 - 0,87				G3/8	lb 0,33				Psi 3625	inch 1,18 2,52 - 0,87				G3/8	lb 0,33	
QC ISO A G 1/2 MALE	12,5	MPa 35	mm - 44 20,5 27					kg 0,0924	NC01G030000	QC ISO A G 1/2 MALE	12,5	MPa 25	mm - 46 20,5 27					kg 0,0924	NC01G030001
		Psi 5075	inch - 1,73 0,81 1,06				G1/2	lb 0,20				Psi 3625	inch - 1,81 0,81 1,06				G1/2	lb 0,20	
QC ISO A G 1/2 FEMALE	12,5	MPa 35	mm 38,25 66 - 27					kg 0,227	NC02G030000	QC ISO A G 1/2 FEMALE	12,5	MPa 25	mm 38 73 - 27					kg 0,227	NC02G030001
		Psi 5075	inch 1,51 2,60 - 1,06				G1/2	lb 0,50				Psi 3625	inch 1,50 2,87 - 1,06				G1/2	lb 0,50	
QC ISO A G 3/4 MALE	20	MPa 25	mm - 55,5 29,1 34					kg 0,2	NC01G040000	QC ISO A G 3/4 MALE	20	MPa 25	mm - 54 29,1 36					kg 0,2	NC01G04S000
		Psi 3625	inch - 2,19 1,15 1,34				G3/4	lb 0,44				Psi 3625	inch - 2,13 1,15 1,42				G3/4	lb 0,44	
QC ISO A G 3/4 FEMALE	20	MPa 25	mm 48 83 - 34					kg 0,49	NC02G040000	QC ISO A G 3/4 FEMALE	20	MPa 25	mm 48 87,5 - 36					kg 0,49	NC02G04S000
		Psi 3625	inch 1,89 3,27 - 1,34				G3/4	lb 1,08				Psi 3625	inch 1,89 3,44 - 1,42				G3/4	lb 1,08	
QC ISO A G 1 MALE	25	MPa 25	mm - 66 34,34 41					kg 0,311	NC01G050000	QC ISO A G 1 MALE	25	MPa 20	mm - 63 34,3 41					kg 0,311	NC01G050001
		Psi 3625	inch - 2,60 1,35 1,61				G 1	lb 0,69				Psi 2900	inch - 2,48 1,35 1,61				G 1	lb 0,69	
QC ISO A G 1 FEMALE	25	MPa 25	mm 56 100 - 41					kg 0,7825	NC02G050000	QC ISO A G 1 FEMALE	25	MPa 20	mm 54 103 - 38					kg 0,7825	NC02G050001
		Psi 3625	inch 2,20 3,94 - 1,61				G 1	lb 1,73				Psi 2900	inch 2,13 4,06 - 1,50				G 1	lb 1,73	
QC ISO A G 1 1/4 MALE	31,5	MPa 25	mm - 74,8 45 50					kg 0,537	NC01G060000	QC ISO A G 1 1/4 MALE	31,5	MPa 10	mm - 69 45 50					kg 0,537	NC01G06S000
		Psi 3625	inch - 2,94 1,77 1,97				G 1 1/4	lb 1,18				Psi 1450	inch - 2,72 1,77 1,97				G 1 1/4	lb 1,18	
QC ISO A G 1 1/4 FEMALE																			